ENABLE

SLATE EXPERTS



DEL PRADO SLATE

STRIKING NATURAL GLIMMERING SLATE

TECHNICAL DATA

Size (overall)	500 x 250 mm 500 x 300 mm
Minimum Pitch	22.5°
Maximum Pitch	90°
Minimum Gauge	150 mm
Minimum Gauge	190 mm
Covering Capacity (net) **500 x 250 mm**	
At Max Gauge	20 slates/m²
Weight	
Per 1000 slates	1.235 tonnes
At max gauge	36.5 kg/m²
Battens Required	
At max gauge	5 m/m²
Minimum Batten Sizes	
Rafter centres up to 600 mm	50 x 25 mm
Nail Size	38 x 3.15 mm
Number of Slates per Pallet	Approx 700

Note: Other size available on request.

This is a guide and covers the majority of the conditions in New Zealand. For a full range of technical data specific to your location and project please contact Enable Slate Experts.

Del Prado"' slate is mined from one of the largest quarries in North West Spain.

PROVEN AND AWARDED

In addition to passing SSQ's own, rigorous quality-control tests, Del Prado roofing slate has been tested in accordance with EN12326, carries the CE marking and is classified as 'A1, T1, S1 '.
It has also been tested to the rigorous Norm Francais (NF228).

APPEARANCE

Del Prado"' First roofing slate has a distinctive riven texture; the deep blue-black colour is totally natural and will not fade, even in the strongest sunlight.

GUARANTEED

Del Prado" First roofing slate is covered by a 75-year guarantee.

ENABLE

SLATE EXPERTS

P 0800 100 172
E hello@enableslate.co.nz

251 Styx Mill Road
Casebrook
Christchurch 8051

www.enableslate.co.nz