

ENABLE

SLATE EXPERTS

MATACOUTA SLATE

THE COST-EFFECTIVE NATURAL SPANISH SLATE

TECHNICAL DATA

Size (overall)	400 x 250 mm 300 x 200 mm
Minimum Pitch	22.5°
Maximum Pitch	90°
Minimum Gauge	150 mm
Minimum Gauge	190 mm
Covering Capacity (net) **500 x 250 mm**	
At Max Gauge	18 slates/m²
Weight	
Per 1000 slates	1.235 tonnes
At max gauge	36.5 kg/m²
Battens Required	
At max gauge	5.0 m/m²
Minimum Batten Sizes	
Rafter centres up to 600 mm	50 x 25 mm
Nail Size	25 x 3 mm
Number of Slates per Pallet	Approx 700

This is a guide and covers the majority of the conditions in New Zealand. For a full range of technical data specific to your location and project please contact Enable Slate Experts.



Matacouta slate is mined from the Matacouta quarries in North West Spain. It is a slightly thicker and lower cost slate.

APPEARANCE

Matacouta roofing slate has a deep blue-black colour and a traditional riven texture. The colour is totally natural and will not fade, even in the strongest sunlight or harshest environments.

GUARANTEED

Matacouta is covered by a 75 year guarantee.

ENABLE

SLATE EXPERTS

P 0800 100 172
E hello@enableslate.co.nz

251 Styx Mill Road
Casebrook
Christchurch 8051

www.enableslate.co.nz